

7-Position Vari-Flo Control Valve
allows you to easily dial any of the 7-valve/filter functions for easier operation and maximum efficiency

Flange Clamp
allows 360° rotation of valve to simplify plumbing

Balance Diffuser
for even water distribution

Advanced Underdrain System
for smooth efficient flow and totally balanced backwashing

Filter Tank
made of rugged, colorfast polymeric material for dependable, all-weather performance and 50 psi (3.5 bar) working pressure

Integral Bottom Drain
Large size for rapid draining

One-piece Molded Design
including integral molded-in base



The SwimPro filtration system offers full-flow technology that provides crystal clear water and good, clean fun for the entire family.



Underdrain Features and Benefits

- Innovative design
- Engineered for full-flow
- Balanced backwashing
- No service assembly

Performance Data

Model	Filtration Area	Design Flow Rate	Pressure Loss at Design Flow Rate	Turnovers 8 Hours	Sand Required
	M ² (FT ²)	M ³ /H (GPM)	Bars (PSI)	M ³ (Gallons)	kgs. (lbs.)
VL210T 520 mm (21")	0.20 (2.15)	10.2 (35)	0.01 (1.73)	81.6 (16,800)	65 (150)
VL240T 600 mm (24")	0.29 (3.12)	11.3 (50)	0.02 (3.46)	90.4 (24,000)	90 (200)
VL270T 685 mm (27")	0.34 (3.66)	13.6 (60)	0.03 (5.19)	108.8 (28,800)	133 (300)



Vari-Flo™ 7-Position Control Valve
with easy-to-use lever-action handle lets you "dial" any of seven valve/filter functions

